

## FIBERGLASS SLEEVING - Heat Treated - Expanding



### FEATURES

- Temperature Range - -40°C to 600°C  
-40°F to 1100°F
- 100% Fiberglass - Woven
- Expandible
- Very Flexible
- Poor Moisture protection
- Flammability - Self Extinguishing (VW-1)

### APPLICATIONS

- Heater Leadwire protection.
- High Temperature Wire Harnesses

### STOCK - 1100°F(600°C) - Fiberglass Sleeving

PART#	COLORS	ID	Wall Thickness	SPOOL SIZE
SLEEVE-F/600C-3	White	3mm (0.118")	0.2mm(0.008")	100m(328ft)
SLEEVE-F/600C-4	White	4mm (0.157")	0.3mm(0.012")	100m(328ft)
SLEEVE-F/600C-6	White	6mm (0.236")	0.3mm(0.012")	100m(328ft)
SLEEVE-F/600C-8	White	8mm (0.315")	0.35mm(0.014")	50m(164ft)
SLEEVE-F/600C-10	White	10mm (0.394")	0.35mm(0.014")	50m(164ft)
SLEEVE-F/600C-12	White	12mm (0.472")	0.35mm(0.014")	50m(164ft)

PART#	COLORS	ID	Wall Thickness	SPOOL SIZE
SLEEVE-F/600C-15	White	15mm (0.591")	0.43mm(0.017")	50m(164ft)
SLEEVE-F/600C-18	White	18mm (0.709")	0.43mm(0.017")	50m(164ft)
SLEEVE-F/600C-20	White	20mm (0.787")	0.43mm(0.017")	50m(164ft)
SLEEVE-F/600C-25	White	25mm (0.984")	0.43mm(0.017")	50m(164ft)
SLEEVE-F/600C-30	White	30mm (1.181")	0.43mm(0.017")	50m(164ft)

## FIBERGLASS SLEEVING - Silicone-Coated - Non-Expanding



### FEATURES

- Temperature Range - -40°C to 200°C(Silicone), F/G (600°C)  
-40°F to 392°F (Silicone), F/G (1100°F)
- Fiberglass - Woven, Silicone extrusion coating
- NON-Expandible
- Flexible
- Excellent Moisture protection
- Flammability - Self Extinguishing (VW-1)
- Dielectric rating - 2500V

### APPLICATIONS

- Heater Leadwire protection.

### STOCK - 392°F(200°C) - Fiberglass Sleeving - Silicone Coating

PART#	COLOR	ID	Wall Thickness	SPOOL SIZE
SLEEVE-F/S2.5K-1.0	White	1.0mm (0.039")	0.40mm(0.0016")	100m(328ft)
SLEEVE-F/S2.5K-1.5	White	1.5mm (0.059")	0.40mm(0.0016")	100m(328ft)
SLEEVE-F/S2.5K-2.0	White	2.0mm (0.079")	0.40mm(0.0016")	100m(328ft)
SLEEVE-F/S2.5K-2.5	White	2.5mm (0.098")	0.40mm(0.0016")	100m(328ft)
SLEEVE-F/S2.5K-3.0	White	3.0mm (0.118")	0.40mm(0.0016")	100m(328ft)
SLEEVE-F/S2.5K-4.0	White	4.0mm (0.158")	0.45mm(0.0018")	100m(328ft)
SLEEVE-F/S2.5K-5.0	White	5.0mm (0.200")	0.45mm(0.018")	100m(328ft)
SLEEVE-F/S2.5K-6.0	White	6.0mm (0.236")	0.50mm(0.020")	100m(328ft)
SLEEVE-F/S2.5K-7.0	White	7.0mm (0.275")	0.50mm(0.020")	100m(328ft)

PART#	COLOR	ID	Wall Thickness	SPOOL SIZE
SLEEVE-F/S2.5K-8.0	White	8.0mm (0.039")	0.60mm(0.0024")	50m(164ft)
SLEEVE-F/S2.5K-9.0	White	9.0mm (0.059")	0.60mm(0.0024")	50m(164ft)
SLEEVE-F/S2.5K-10	White	10mm (0.098")	0.60mm(0.0024")	50m(164ft)
SLEEVE-F/S2.5K-12	White	12mm (0.118")	0.60mm(0.0024")	50m(164ft)
SLEEVE-F/S2.5K-16	White	16mm (0.158")	0.70mm(0.0028")	50m(164ft)
SLEEVE-F/S2.5K-20	White	20mm (0.200")	0.70mm(0.0028")	50m(164ft)
SLEEVE-F/S2.5K-25	White	25mm (0.236")	0.70mm(0.0028")	50m(164ft)
SLEEVE-F/S2.5K-30	White	30mm (0.275")	0.70mm(0.0028")	50m(164ft)