

DIGITAL COMBINATION CONTROL PANELS



FEATURES

- Provides precise digital control for consistent plating and etch rates in most aqueous processes
- Available in single or three phases
- Large and easy-to-read LED display
- Includes a fluoropolymer (FEP) covered 10-foot (3m), Type J sensor as standard
- Vapor resistant, NEMA 1, IP21, gasketed 1/8 DIN plastic enclosure
- Large switching capacity ranging from 20-125 amps up to 600 volts
- Adjustable temperature range from -40°F (-40°C) to 1000°F (538°C)
- Includes Overtemperature safety circuit with manual reset pushbutton
- Mounted in NEMA 12 Polycarbonate Enclosure



RUSH OPTIONS

- 7 DAY EXPEDITE
- 3-5 DAY EXPEDITE
- 1 DAY EXPEDITE

STANDARD PARTS

MODEL NUMBER	VOLTS	MAX AMPS
PANEL-TCD240*/20A	240V	20A
PANEL-TCD480*/20A	480V	20A
PANEL-TCD240*/40A	240V	40A
PANEL-TCD480*/40A	480V	40A
PANEL-TCD240*/80A	240V	80A
PANEL-TCD480*/80A	480V	80A
PANEL-TCD240*/125A	240V	125A
PANEL-TCD480*/125A	480V	125A

2-3 Week Lead Time for Standard & Custom Products!

ORDER CODE

PANEL-TCDXXX	/	X	/	XXX	STANDARD OPTIONS
VOLTAGE		NUMBER OF PHASES		AMPERES	
240 - 240V		1 - SINGLE PHASE		20 - 20A	R - PT100RTD SENSOR
480 - 480V		3 - THREE PHASE		40 - 40A	R1000 - PT1000RTD SENSOR
600 - 600V				80 - 80A	L - NO SENSOR
208 - 208V				125 - 120A	25 - 25FT TYPE J THERMOCOUPLE
220 - 220V				Other	50 - 50FT TYPE J THERMOCOUPLE
Other					Other