



# 3/4" WIDE HIGH TEMPERATURE HEATER



## STANDARD FEATURES

<b>Single Ended</b>	Terminal Block/Wire Leads
<b>Length</b>	Custom (Standard Range: 12.5" - 54")
<b>Watts</b>	500 - 3,000 W"
<b>Volts</b>	120, 240, and 480 V
<b>Watt Density</b>	24 - 38 W/in <sup>2</sup>
<b>Max Temp</b>	1500°F (816°C)

## INFORMATION

**Durable Construction:** Built with high-quality INCOLOY®, our heater offers exceptional durability and longevity. It is resistant to thermal shock and wear, ensuring a longer lifespan and reduced maintenance costs.

**Versatile Applications:** Suitable for a wide range of uses, including plastics processing, food service, and laboratory equipment. Its design allows for seamless integration into various setups.

**Efficient Heat Distribution:** We optimize heat distribution, minimizing hot spots and ensuring uniform heating across surfaces.

**Easy Installation:** Designed with user-friendliness in mind, the heater can be easily integrated into existing systems.

**Safety Features:** Our control panels have built-in safety mechanisms, including overheat protection and thermal cutoffs, our heaters prioritize safety for your peace of mind.

**Exceptional Customer Support:** Our commitment to your satisfaction goes beyond the sale. Our

## DIMENSIONS

