



CALIBRATION

Type J Type E
 Type K
 Type T

LEAD LENGTH (SPECIFY)

Length:

Units:

JUNCTION

Grounded (standard)
 Exposed

REQUIRED LEAD TIME

1.5-2 weeks (standard)
 1 week expedited mfg
 3-4 days expedited mfg
 1-2 days expedite mfg
 Same day expedited mfg

LEAD WIRE MATERIAL

Fiberglass (800°F)
 Teflon (400°F)
 Kapton (500°F)
 High temperature fiberglass (1200°F)
 Fiberglass with stainless steel braid (800°F) (standard)
 Teflon with stainless steel braid (400°F)
 Ceramic fiber with Inconel Braid (2100°F)

TERMINATIONS/OPTIONS

Stripped Leads	1/4 inch push-on connector
Fork Terminals	Ceramic Male Plug (1200°F)
Standard male plug (400°F)	Ceramic Female Plug (1200°F)
Standard female jack (400°F)	Ceramic mini Male Plug (1200°F)
Miniature male plug (400°F)	Ceramic mini Female Jack (1200°F)
Miniature female jack (400°F)	

SPECIAL FEATURES

None
 Solid conductor (Lead wire)
 Cable Clamp
 Bx Connector
 Mating connector
 Moisture protection boot on connector
 Add ground wire to TC & RTD