



CERAMIC STRIP HEATERS



INFORMATION

DIMENSIONS: 1½" WIDE, 5/16" OR 3/8" THICK, UP TO 72" LONG
 5/16" X ½" MOUNTING SLOTS (CENTER/CENTER) = OVERALL LENGTH - ¾"

MAX WATTAGE: 120 WATTS / INCH OF HEATED LENGTH,
 75 IF ONLY ONE SIDE IS IN CONTACT.

MAX WATT DENSITY: 75 W/LINEAR INCH.
 120 IF 2 SIDES IN CONTACT WITH PART

MAX VOLTAGE: 300V STANDARD,
 480V SPECIAL

MAX TEMPERATURE: 1200°F

MAX AMPS (LEADS) 12A

MAX AMPS (TERMINALS) 20A

CONSTRUCTION TYPES/ ELECTRICAL TERMINATIONS

SL1-no-tab Fiberglass	SB1-no-tab Fiberglass + S/S Braid	SL4-no-tab Fiberglass	SL4-tab Fiberglass	SB4-no-tab Fiberglass + S/S Braid
SB4-tab Fiberglass + S/S Braid	SC4-tab Fiberglass + S/S Armour	SN1-no-tab Post Terminals	SN1-tab Post Terminals	SN2-no-tab Post Terminals
SN2-tab Post Terminals	SN3-no-tab Post Terminals	SN3-tab Post Terminals	SN4-no-tab Post Terminals	SN4-tab Post Terminals