




ADJUSTABLE BAYONET THERMOCOUPLE W/ FLEXIBLE ARMOR



CALIBRATION

Type J	Type T
Type K	Type E

CAP SIZE

7/16"ID Single Slot (1/4"OD Spring)
 12.5mmID Double Slot (1/4"OD Spring)
 14.7mmID Double Slot (1/4"OD Spring)

LEAD LENGTH (SPECIFY)

Length:

Units:

SHEATH LENGTH

1/4"	5/8"	1.25"	2"
3/8"	Y 3/4"	1.5"	
1/2"	1"	1.75"	

JUNCTION

Grounded, flat tip
 Grounded, round tip
 Grounded, drill point
 Ungrounded, round tip
 Ungrounded, drill point
 Ungrounded, flat tip

REQUIRED LEAD TIME

1.5-2 weeks (standard)
 1 week expedited mfg
 3-4 days expedited mfg
 1-2 days expedite mfg
 Same day expedited mfg

SHEATH DIAMETER

0.118" (3mm)	0.236" (6mm)
0.125" (3.2mm) (1/8")	0.250" (6.4mm) (1/4")
0.156" (4mm)	0.314" (8mm) (5/16")
0.188" (4.8mm) (3/16") (standard)	Custom

LEAD WIRE MATERIAL

Fiberglass (800°F)
 Teflon (400°F)
 Kapton (500°F)
 High temperature fiberglass (1200°F)
 Fiberglass with stainless steel braid (800°F) (standard)
 Teflon with stainless steel braid (400°F)

TERMINATIONS/OPTIONS

Stripped Leads	1/4 inch push-on connector
Fork Terminals	Ceramic Male Plug (1200°F)
Standard male plug (400°F)	Ceramic Female Plug (1200°F)
Standard female jack (400°F)	Ceramic mini Male Plug (1200°F)
Miniature male plug (400°F)	Ceramic mini Female Jack (1200°F)
Miniature female jack (400°F)	

SPECIAL FEATURES

None	Mating connector
Solid conductor (Lead wire)	Moisture protection boot on connector
Flat tip probe	Add ground wire to TC & RTD
Drill point tip	Silver solder thermocouple junction
Epoxy seal	
Cable clamp	
Bx connector	