



ELEMENT TYPE

- 100 Ω
- 120 Ω
- 1000 Ω
- 10 Ω
- 500 Ω

WIRE CONFIGURATION

- 2-wire
- 4-wire
- 3-wire
- 3-wire (Dual)
- 2-wire (Dual)

TIP LENGTH

- 1/4"
- 5/8"
- 1-1/8"
- 3/8"
- 3/4"
- 1-1/4"
- 1/2"
- 1"
- Custom

MELT BOLT LENGTH

- 3"
- 7"
- 14"
- 4"
- 9"
- Custom
- 6"
- 12"

REQUIRED LEAD TIME

- 1.5-2 weeks (standard)
- 1 week expedited mfg
- 3-4 days expedited mfg
- 1-2 days expedite mfg
- Same day expedited mfg

TIP DIAMETER

- 0.118" (3mm)
- 0.125" (3.2mm) (1/8")
- 0.156" (4mm)
- 0.188" (4.8mm) (3/16") (standard)
- 0.236" (6mm)
- 0.250" (6.4mm) (1/4")
- Custom

STYLE

- (Style 2) No Lead Wire – Rigid Style
- (Style 1) Fiberglass with armor cable
- (Style 1) Fiberglass with Stainless steel braid

TERMINATIONS/OPTIONS

- Stripped Leads
- Fork Terminals
- Standard male plug (400°F)
- Standard female jack (400°F)
- Miniature male plug (400°F)
- Miniature female jack (400°F)