



ELEMENT TYPE

- 100 Ω
- 120 Ω
- 1000 Ω
- 10 Ω
- 500 Ω

WIRE CONFIGURATION

- 2-wire
- 4-wire
- 3-wire
- 3-wire
- 2-wire (Dual)
- (Dual)

SHEATH CONFIGURATION

- Straight
- 45°
- 90°

INSERTION LENGTH

Length:

Units:

SHEATH LENGTH

Length:

Units:

SHEATH DIAMETER

- 0.118" (3mm)
- 0.125" (3.2mm) (1/8")
- 0.156" (4mm)
- 0.188" (4.8mm) (3/16") (standard)
- 0.236" (6mm)
- 0.250" (6.4mm) (1/4")
- 0.314" (8mm) (5/16")
- Custom – Specify in Message

WIRE MATERIAL

- Fiberglass (800°F)
- Teflon (400°F)
- Kapton (500°F)

TERMINATIONS/OPTIONS

- Stripped Leads
- Fork Terminals
- Standard male plug (400°F)
- Standard female jack (400°F)
- Miniature male plug (400°F)
- Miniature female jack (400°F)

SPECIAL FEATURES

- None
- Flat tip probe
- Drill point tip
- Mating connector
- Moisture protection boot on connector
- Fluoropolymer covered probe
- Free spinning fitting (held on probe by a crimp ring)



RIGID SHEATH WITH OPTIONAL FITTING RTDS

REQUIRED LEAD TIME

- 1.5-2 weeks (standard)
- 1 week expedited mfg
- 3-4 days expedited mfg
- 1-2 days expedite mfg
- Same day expedited mfg

ATTACHED FITTING (OPTIONAL)

- None
- 1/8" npt single thread
- 1/4" npt single thread
- 3/8" npt single thread
- 1/2" npt single thread
- 3/4" npt single thread
- 1/2" npt x 1/2" npt double thread
- 1/2" npt double thread. Spring loaded
- 1/2" npt x 1/2" npt double thread. Spring loaded w/ oil seal
- 1/2" npt x 3/4" npt double thread
- 3/4" npt x 3/4" npt double thread
- Adjustable 7/16" ID bayonet cap fitting (1/8" OD & 3mm OD)
- Adjustable 12.5mm ID double slot bayonet cap fitting(1/8" OD & 3mm OD)
- 1/8" npt compression fitting (Brass)
- 1/8" npt compression fitting (Stainless Steel)
- 1/4" npt compression fitting (Brass)
- 1/4" npt compression fitting (Stainless Steel)
- 1/4" npt double thread