



## CALIBRATION

Type J	Type J (Dual)
Type K	Type K (Dual)
Type T	Type T (Dual)
Type E	Type E (Dual)

## LEAD LENGTH (SPECIFY)

Length:

Units:

## SPECIAL FEATURES

- None
- Solid conductor (Lead wire)
- Cable Clamp
- Bx Connector
- Mating connector
- Moisture protection boot on connector

## REQUIRED LEAD TIME

- 1.5-2 weeks (standard)
- 1 week expedited mfg
- 3-4 days expedited mfg
- 1-2 days expedite mfg
- Same day expedited mfg

## LEAD WIRE MATERIAL

PVC (220°F)	Fiberglass with armor cable (800°F)
Fiberglass (800°F)	Teflon with armor cable (400°F)
Teflon (400°F)	Fiberglass with stainless steel braid with armor cable (800°F)
Kapton (500°F)	Teflon with stainless steel braid with armor cable (400°F)
High temperature fiberglass (1200°F)	Ceramic fiber with Inconel weld (2100°F)
Fiberglass with stainless steel braid (800°F) (Standard)	
Teflon with stainless steel braid (400°F)	

## TERMINATION 1

Stripped Leads	1/4 inch push-on connector
Fork Terminals	Ceramic Male Plug (1200°F)
Standard male plug (400°F)	Ceramic Female Plug (1200°F)
Standard female jack (400°F)	Ceramic mini Male Plug (1200°F)
Miniature male plug (400°F)	Ceramic mini Female Jack (1200°F)
Miniature female jack (400°F)	

## TERMINATION 2

Stripped Leads	1/4 inch push-on connector
Fork Terminals	Ceramic Male Plug (1200°F)
Standard male plug (400°F)	Ceramic Female Plug (1200°F)
Standard female jack (400°F)	Ceramic mini Male Plug (1200°F)
Miniature male plug (400°F)	Ceramic mini Female Jack (1200°F)
Miniature female jack (400°F)	