



NAME:

### CALIBRATION

- Type J
- Type K
- Type T
- Type E

### LEAD LENGTH (SPECIFY)

Length:

Units:

### LEAD WIRE MATERIAL

- Fiberglass (800°F)
- Teflon (400°F)
- Kapton (500°F)
- High temperature fiberglass (1200°F)
- Fiberglass with stainless steel braid (800°F)
- Teflon with stainless steel braid
- (400°F)
- Fiberglass with armor cable (800°F) (standard)
- Teflon with armor cable (400°F)
- Fiberglass with stainless steel braid with armor cable (800°F)
- Teflon with stainless steel braid with armor cable (400°F)

### JUNCTION

- Grounded (standard)
- Exposed

### GROMMET STYLE

- Style 1 1/4" ID x 0.545" OD x 1.14" long
- Style 2 1/4" ID x 0.545" OD (No ring terminal)

### QUANTITY

### REQUIRED LEAD TIME

- 1.5-2 weeks (standard)
- 1 week expedited mfg
- 3-4 days expedited mfg
- 1-2 days expedite mfg
- Same day expedited mfg

### TERMINATIONS/OPTIONS

- Stripped Leads
- Fork Terminals
- Standard male plug (400°F)
- Standard female jack (400°F)
- Miniature male plug (400°F)
- Miniature female jack (400°F)
- 1/4 inch push-on connector
- Ceramic Male Plug (1200°F)
- Ceramic Female Plug (1200°F)
- Ceramic mini Male Plug (1200°F)
- Ceramic mini Female Jack (1200°F)

### SPECIAL FEATURES

- None
- Solid conductor (Lead wire)
- Cable Clamp
- Bx Connector
- Mating connector
- Moisture protection boot on connector
- Add ground wire to TC & RTD